

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 820 701 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

28.01.1998 Bulletin 1998/05

(51) Int. Cl.⁶: **A23G 1/20**

(21) Application number: 97111239.6

(22) Date of filing: 04.07.1997

(84) Designated Contracting States:

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE

(30) Priority: 23.07.1996 GB 9615403

(71) Applicant:

SOCIETE DES PRODUITS NESTLE S.A.
1800 Vevey (CH)

(72) Inventors:

- **Jury, Mark**
Thirsk, North Yorkshire YO7 2PH (GB)
- **Mackley, Malcolm Robert**
Crescent, Cambridge CB4 1AP (GB)
- **Crook, Simon John**
Exeter, Devon EX4 4AF (GB)

(74) Representative:

Pate, Frederick George et al
55, Avenue Nestlé
1800 Vevey (CH)

(54) Extrusion of chocolate

(57) A process for plastically extruding a fat-containing confectionery material which comprises feeding the fat containing confectionery material into an extruder and applying pressure to the fat-containing confectionery material in a substantially solid or semi-solid non-pourable form upstream of a flow constriction whereby the temperature, pressure, contraction ratio and extrusion rate are such that the fat-containing confectionery material is extruded and remains in a substantially solid or semi-solid nonpourable form to produce an axially

homogeneous extruded product having a cross section that is of substantially the same profile as the die exit of the extruder, which is capable of retaining its shape and which has a temporary flexibility or plasticity enabling it to be physically manipulated, cut or plastically deformed before losing its flexibility or plasticity characterised in that a vacuum is applied to the fat-containing confectionery material upstream of the flow constriction.




FIG. 1

EP 0 820 701 A2

Description

The present invention relates to the extrusion of chocolate and more particularly to a process for the extrusion of solid or semi-solid chocolate.

In our co-pending EP-A-93114251.7, the entirety of which is hereby incorporated by reference, we describe a process for plastically extruding a fat-containing confectionery material which comprises feeding the fat containing confectionery material into an extruder and applying pressure to the fat-containing confectionery material in a substantially solid or semi-solid nonpourable form upstream of a flow constriction whereby the temperature, pressure, contraction ratio and extrusion rate are such that the fat-containing confectionery material is extruded and remains in a substantially solid or semi-solid nonpourable form to produce an axially homogeneous extruded product having a cross section that is of substantially the same profile as the die exit of the extruder, which is capable of retaining its shape and which has a temporary flexibility or plasticity enabling it to be physically manipulated, cut or plastically deformed before losing its flexibility or plasticity.

In GB-A-96 06285, the entirety of which is hereby incorporated by reference, we describe a process for the continuous extrusion of chocolate or a fat-containing confectionery material using a screw extruder which comprises feeding the chocolate or fat-containing confectionery material into the screw extruder and generating a pressure to force the chocolate or fat-containing confectionery material in a substantially solid or semi-solid nonpourable form upstream of a flow constriction whereby the temperature of the screw, the temperature of the barrel wall, the screw speed, pressure, contraction ratio and extrusion rate are such that the chocolate or fat-containing confectionery material is extruded in a substantially solid or semi-solid nonpourable form to produce an axially homogeneous extruded product having a cross section that is of substantially the same profile as the die exit of the extruder, which is capable of retaining its shape and which has a temporary flexibility or plasticity enabling it to be physically manipulated, cut or plastically deformed before losing its flexibility or plasticity.

The temporary flexibility of the extruded fat-containing confectionery material obtained in the process of the above-mentioned co-pending patent application may last for up to 4 hours or more, generally from 0.1 second to 2 hours or typically from 10 seconds to 1 hour. During this period of temporary flexibility, the extruded fat-containing confectionery material may be cut cleanly and this is in contrast to fat-containing confectionery material extruded by a process as described either in EP-A-93114251.7 or in GB-A-96 06285 after the temporary flexibility has been lost, or to a normal set chocolate which has to be heated slightly for cutting otherwise it would shatter owing to its brittleness. However, the appearance of the chocolate is not always as attractive

as desired because there may be whitish streaks or blotches on both the exterior surface and on the cut surface. The streaks or blotches give a streaky pattern similar to mouldy cheese.

Surprisingly, we have found that by applying a vacuum to the chocolate feed upstream of the extruder die, the extruded chocolate has an attractive appearance without or substantially without any streaks or blotches on either the exterior surface or on the cut surface. Although not wishing to be bound by any theory, we believe that the product cohesiveness is improved owing to a reduction of the trapped air spaces in the product.

Accordingly, the present invention provides a process for plastically extruding a fat-containing confectionery material which comprises feeding the fat containing confectionery material into an extruder and applying pressure to the fat-containing confectionery material in a substantially solid or semi-solid nonpourable form upstream of a flow constriction whereby the temperature, pressure, contraction ratio and extrusion rate are such that the fat-containing confectionery material is extruded and remains in a substantially solid or semi-solid nonpourable form to produce an axially homogeneous extruded product having a cross section that is of substantially the same profile as the die exit of the extruder, which is capable of retaining its shape and which has a temporary flexibility or plasticity enabling it to be physically manipulated, cut or plastically deformed before losing its flexibility or plasticity characterised in that a vacuum is applied to the fat-containing confectionery material upstream of the flow constriction.

Before being fed into the extruder, the fat containing confectionery material may be stored in a hopper or other container. The vacuum may be applied to the fat containing confectionery material at any point between the hopper and the infeed of the extruder or while the fat-containing confectionery material is being fed into the extruder. Optionally, a valve, preferably a rotary valve, may be present between the hopper or other container and the infeed of the extruder. The vacuum pressure may be as low as 1mbar or less but is more conveniently from 10 to 500mbar and preferably from 50 to 300 mbar.

The fat containing confectionery material may be fed into the barrel of the extruder in a solid or semi-solid form, e.g. in a granular or continuous form. When in granular form, the granular nature of the fat containing confectionery material appears to be lost during extrusion to give an essentially uniform material. The extruded material can be cut cleanly during the post-extrusion period of temporary flexibility or plasticity.

The extruder may be a ram extruder, a single screw extruder, a twin screw extruder or a Conform machine. The twin screw extruder may have either counter-rotating screws or co-rotating screws. The process may be continuous when a screw extruder is used.

When a screw extruder is used, the conditions of

the screw extrusion may be as described in GB-A-96 06285.

The chocolate material may be dark, milk or white chocolate. Fat containing confectionery materials may include sugar, milk derived components, and fat and solids from vegetable or cocoa sources in differing proportions having a moisture content less than 10%, more usually less than 5% by weight. They may be chocolate substitutes containing direct cocoa butter replacements, stearines, coconut oil, palm oil, butter or any mixture thereof; nut pastes such as peanut butter and fat; praline; confectioner's coatings used for covering cakes usually comprising chocolate analogues with cocoa butter replaced by a cheaper non-tempering fat; or "Caramac" sold by Nestlé comprising non-cocoa butter fats, sugar and milk.

If desired, two or more fat-based confectionery materials may be extruded in accordance with the process of the present invention. In addition, the chocolate or fat-containing confectionery material may be co-extruded with other food materials such as ice cream, sorbet, yoghurt, mousse, fondant, praline, marshmallow, nougat or jelly, etc., such being advantageous when the fat-containing confectionery material is extruded in a hollow or tubular form. Hence, in such embodiments, a multi-orifice die and/or associated equipment, as are known to those skilled in the art, may be employed.

The temperature of the chocolate or fat-containing confectionery material as it is extruded may conveniently be from 0° to 28°C, more usually from 15 to 25°C, e.g. from 18° to 23°C.

The present invention will now be further described by way of example only with reference to the accompanying drawing in which Figure 1 represents a schematic diagram of a continuous extrusion system.

Referring to Figure 1, the extruder generally designated 10 comprises a barrel 11 provided with a cooling jacket 12 having an inlet for cooling fluid 13 and an outlet for cooling fluid 14, an inlet for the feed material to be extruded 15, a die 16 having a circular cross-section and a diameter of 6.5mm, and a screw 17 whose root diameter increases from the upstream end to the downstream end and provided with threads 18 whose pitch is constant from the upstream end to the downstream end. The screw 17 is provided with a channel 19 for heating fluid extending from the upstream end to the downstream end having an inlet 20 connected with a concentric channel 21 leading to an outlet for the heating fluid 22. Positioned above the inlet for the feed material to be extruded 15 is a hopper 23, a rotary valve 24 and a connecting pipe 25 leading to a means for applying a vacuum 25 (not shown).

The operation of the above described single screw extruder will now be described in the following Examples.

Example 1

Milk chocolate buttons in the hopper 23 having a temperature of 22°C are fed via the rotary valve 24 into the barrel 11 of the extruder 10 through the feed inlet 15. Positioned between the rotary valve 24 and the feed inlet 15 is a pipe 25 leading to a vacuum pump (not shown) which applies a vacuum pressure of 100mbar to the chocolate buttons. The screw 17 has a diameter of 32mm, a length to diameter ratio of 24:1, a 2:1 compression ratio and a screw speed of 65rpm. A 50:50 mixture of water and glycol at -5°C flows through the cooling jacket 12 of the barrel and water at 20°C flows through the channels 19 and 21 of the screw. As the screw rotates, the solid chocolate flows through at a rate of 15kg/hr and is extruded through the die 16 with a configuration conforming to that of the die and has a temporary flexibility which lasts for about 1 hour. The extruded chocolate is cut 1 minute after extrusion and exhibits no streaks or blotches on its exterior or cut surfaces.

Example 2

Milk chocolate buttons in the hopper 23 having a temperature of 22°C are fed via the rotary valve 24 into the barrel 11 of the extruder 10 through the feed inlet 15. Positioned between the rotary valve 24 and the feed inlet 15 is a pipe 25 leading to a vacuum pump (not shown) which applies a vacuum pressure of 100mbar to the chocolate buttons. The screw 17 has a diameter of 90mm, a length to diameter ratio of 15:1, a 2:1 compression ratio and a screw speed of 35rpm. Water at 5°C flows through the cooling jacket 12 of the barrel and water at 20°C flows through the channels 19 and 21 of the screw. As the screw rotates, the solid chocolate flows through at a rate of 280kg/hr and is extruded through the die 16 with a configuration conforming to that of the die and has a temporary flexibility which lasts for about 1 hour. The extruded chocolate is cut within 1 second after extrusion and exhibits no streaks or blotches on its exterior or cut surfaces.

Claims


1. A process for plastically extruding a fat-containing confectionery material which comprises feeding the fat containing confectionery material into an extruder and applying pressure to the fat-containing confectionery material in a substantially solid or semi-solid nonpourable form upstream of a flow constriction whereby the temperature, pressure, contraction ratio and extrusion rate are such that the fat-containing confectionery material is extruded and remains in a substantially solid or semi-solid nonpourable form to produce an axially homogeneous extruded product having a cross section that is of substantially the same profile as the die exit of the extruder, which is capable of

retaining its shape and which has a temporary flexibility or plasticity enabling it to be physically manipulated, cut or plastically deformed before losing its flexibility or plasticity characterised in that a vacuum is applied to the fat-containing confectionery material upstream of the flow constriction. 5

2. A process according to claim 1 wherein before being fed into the extruder, the fat containing confectionery material may be stored in a hopper or other container and the vacuum is applied to the fat containing confectionery material either at any point between the hopper and the infeed of the extruder or while the fat-containing confectionery material is being fed into the extruder. 10 15
3. A process according to claim 2 wherein a valve is present between the hopper or other container and the infeed of the extruder. 20
4. A process according to claim 3 wherein the valve is a rotary valve.
5. A process according to claim 1 wherein the vacuum pressure is from 10 to 500mbar. 25
6. A process according to claim 1 wherein the extruder is a ram extruder, a single screw extruder, a twin screw extruder or a Conform machine. 30
7. A process according to claim 1 wherein the chocolate or fat-containing confectionery material may be co-extruded with another chocolate or fat-based confectionery material or another food material. 35
8. A process according to claim 7 wherein the other food material is ice cream, sorbet, yoghurt, mousse, fondant, praline, marshmallow, nougat, jelly or any other food material. 40
9. An extruded fat-containing confectionery material obtainable by a process according to any of the preceding claims. 45

50

55



(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 820 701 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
08.12.1999 Bulletin 1999/49

(51) Int. Cl.⁶: **A23G 1/20**, **A23G 3/20**

(43) Date of publication A2:
28.01.1998 Bulletin 1998/05

(21) Application number: 97111239.6

(22) Date of filing: 04.07.1997

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE**

(30) Priority: 23.07.1996 GB 9615403

(71) Applicant:
SOCIETE DES PRODUITS NESTLE S.A.
1800 Vevey (CH)

(72) Inventors:
• **Jury, Mark**
Thirsk, North Yorkshire YO7 2PH (GB)
• **Mackley, Malcolm Robert**
Crescent, Cambridge CB4 1AP (GB)
• **Crook, Simon John**
Exeter, Devon EX4 4AF (GB)

(74) Representative:
Pate, Frederick George et al
55, Avenue Nestlé
1800 Vevey (CH)

(54) Extrusion of chocolate

(57) A process for plastically extruding a fat-containing confectionery material which comprises feeding the fat containing confectionery material into an extruder (11-12) and applying pressure to the fat-containing confectionery material in a substantially solid or semi-solid nonpourable form upstream of a flow constriction whereby the temperature, pressure, contraction ratio and extrusion rate are such that the fat-containing confectionery material is extruded and remains in a substantially solid or semi-solid nonpourable form to

produce an axially homogeneous extruded product having a cross section that is of substantially the same profile as the die exit (16) of the extruder, which is capable of retaining its shape and which has a temporary flexibility or plasticity enabling it to be physically manipulated, cut or plastically deformed before losing its flexibility or plasticity characterised in that a vacuum is applied to the fat-containing confectionery material upstream of the flow constriction.




FIG. 1

EP 0 820 701 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 11 1239

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 3 008 184 A (R. FRITSCH) 14 November 1961 (1961-11-14) * column 3, line 19 - line 25; figure *	1-3,9	A23G1/20 A23G3/20
Y	US 5 439 695 A (M.R. MACKEY) 8 August 1995 (1995-08-08) * column 4, line 5 - line 65 * * column 6, line 20 - line 36; figures 6-10; examples *	1-6,9	
Y	US 4 861 615 A (WIEDMANN WERNER) 29 August 1989 (1989-08-29) * column 4, line 4 - line 57; claim 1; figure *	1-6,9	
A	EP 0 277 498 A (WENGER MFG) 10 August 1988 (1988-08-10)		
A	US 4 746 529 A (RAPP RUDOLF) 24 May 1988 (1988-05-24)		
A	US 5 139 806 A (HAUSER THOMAS W ET AL) 18 August 1992 (1992-08-18) * the whole document *	1	TECHNICAL FIELDS SEARCHED (Int.Cl.6) A23G
A	FR 570 732 A (A.D. FISHER) 6 May 1924 (1924-05-06)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 5 October 1999	Examiner Guyon, R
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/02 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 97 11 1239

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-10-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3008184	A	14-11-1961	CH 375520 A	
			DE 1099996 B	
			FR 1253139 A	15-05-1961
			GB 946458 A	
			LU 38223 A	
			NL 124077 C	
			NL 248546 A	
US 5439695	A	08-08-1995	GB 2270828 A	30-03-1994
			AT 144107 T	15-11-1996
			AU 668202 B	26-04-1996
			AU 4628093 A	14-04-1994
			BR 9303944 A	05-04-1994
			CA 2106554 A	30-03-1994
			CN 1090719 A, B	17-08-1994
			CZ 9302032 A	15-12-1994
			DE 69305483 D	21-11-1996
			DE 69305483 T	20-02-1997
			DK 603467 T	24-03-1997
			EP 0603467 A	29-06-1994
			ES 2096820 T	16-03-1997
			HK 48697 A	25-04-1997
			HU 67526 A, B	28-04-1995
			JP 6189683 A	12-07-1994
			MX 9305975 A	31-01-1995
			NZ 248772 A	26-04-1996
			SK 102393 A	08-06-1994
			ZA 9306630 A	29-06-1994
US 4861615	A	29-08-1989	DE 3629526 A	10-03-1988
			DE 3772502 A	02-10-1991
			EP 0262300 A	06-04-1988
			JP 63063344 A	19-03-1988
EP 0277498	A	10-08-1988	US 4769251 A	06-09-1988
			CA 1332536 A	18-10-1994
			JP 63248357 A	14-10-1988
US 4746529	A	24-05-1988	DE 3417126 A	14-11-1985
			AT 45858 T	15-09-1989
			DK 6786 A	08-01-1986
			WO 8505012 A	21-11-1985
			EP 0183745 A	11-06-1986
			FI 854942 A, B	13-12-1985
			JP 61502096 T	25-09-1986

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 11 1239

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-10-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5139806 A	18-08-1992	EP 0471103 A	19-02-1992
		AT 109952 T	15-09-1994
		DE 69011680 D	22-09-1994
		DE 69011680 T	08-12-1994
		DK 471103 T	14-11-1994
		JP 1934089 C	26-05-1995
		JP 4258266 A	14-09-1992
		JP 6069349 B	07-09-1994
<hr/>			
FR 570732 A	06-05-1924	NONE	
<hr/>			

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

